Nanosystems and Technologies GmbH
nanoplus

DFB Quantum Cascade Lasers (QCL): 6000 nm - 11000 nm

WAVELENGTH

- 760–830 nm
- 830–920 nm
- 920–1100 nm
- 1100–1300 nm
- 1300–1650 nm
- 1650–1850 nm
- 1850–2200 nm
- 2200–2600 nm
- 2600–2900 nm
- 2800–4000 nm
- 4000–4600 nm
- 4600–5300 nm
- 5300–5800 nm
- 5800–6500 nm
- **6000–11000 nm**

nanoplus Distributed Feedback Lasers **(DFB)** are specifically designed for high-precision gas detection using tunable diode laser absorption spectroscopy **(TDLAS)**. Our devices operate **reliably** in more than 50,000 installations worldwide. For 25 years nanoplus has set the standard for DFB laser technology and is the only manufacturer routinely providing DFB lasers at **any wavelength.**

Key features:

- MONOMODE
- CONTINUOUS WAVE
- ROOM TEMPERATURE
- MODE HOP FREE TUNING



Schematic DFB with spectrum



Overgrowth-free DFB device processing

Any **custom wavelength** is possible: You tell us what you need and we deliver it. With our patented DFB technology we design any wavelength **between 760 nm and 14 µm.**

Our excellent **spectral purity** is characterized by a large side mode suppression ratio **(SMSR)** of **> 35 dB,** giving your system a low signal to noise ratio against crossinterference.

A **narrow linewidth** **below 3 MHz** guarantees ultra-precise scanning of the absorption line feature. The **high output power** of **several mW** yields a stronger signal and increases your measurement precision.

Fast and wide wavelength tuning is required for in situ systems. Most customers use a scan rate of 10 kHz and benefit from our very **large tuning coefficient.**

"Do not change your ideas, let us deliver a laser that fits your application."

We offer **various** **packaging options,** e.g. several free space housings including TEC and NTC, fiber coupling, **collimation** and **custom designs.** What do you require?

If you require **custom specifications,** please contact us. Nearly 80 % of our devices are more or less customer-specific. As nanoplus is a **fully vertically integrated company,** we control the entire process chain from design to packaging.
Both nanoplus production facilities are based in **Germany.** To guarantee consistent product quality we apply a strict and **ISO certified quality management system** at all levels.

High-Heatload (HHL) mount[1] incl. collimation

Our sales and R&D teams have long-standing experience in developing lasers. They will advise you in your design and realization phase as well as after-sales:
We make market leaders!

REGISTERED COMPANY ISO 9001 14001

CLASS 3B LASER PRODUCT (DIN EN 60825-1) DO NOT VIEW DIRECTLY WITH OPTICAL INSTRUMENTS

ATTENTION OBSERVE PRECAUTION FOR HANDLING ELECTROSTATIC SENSITIVE DEVICES

DANGER LASER RADIATION AVOID DIRECT EXPOSURE TO BEAM CLASS 3B LASER PRODUCT

Nanosystems and Technologies GmbH
nanoplus

Typical Specifications: 6000 nm - 11000 nm

This data sheet reports performance data of a **sample DFB QCL at 7970 nm,** which is representative for the entire wavelength range.



Typical room temperature cw spectrum of a nanoplus DFB QCL at 7970 nm



Typical mode hop free tuning of a nanoplus DFB QCL at 7970 nm by current and temperature

electro-optical characteristics[1]	symbol	unit	min.	typ	max.
operating wavelength (at T_{op}, I_{op})	λ_{op}	nm		Please specify to 0.1 nm.	
optical output power (at λ_{op})	P_{op}	mW	10	20	
operating current	I_{op}	mA		500	1500
operating voltage	V_{op}	V		9	15
threshold current	I_{th}	mA		400	
side mode suppression ratio	SMSR	dB		> 35	
current tuning coefficient	C_I	nm / mA	0.05	0.1	0.15
temperature tuning coefficient	C_T	nm / K		0.7	
operating chip temperature	T_{op}	°C	-10	20	45
operating case temperature[2]	T_c	°C	10	20	30
storage temperature[2]	T_S	°C	0	20	50

[1] TM-polarized [2] non-condensing

packaging

High-Heatload Mount (HHL) incl. collimation

Other packaging options may be discussed on request.

Technical drawings & accessories are available at: nanoplus.com/packaging

Please contact sales@nanoplus.com for customized specifications, quotes and further questions.
Visit our website for technical notes, application samples or literature referrals.

Rev.QCL.7970.08

nanoplus Nanosystems and Technologies GmbH, www.nanoplus.com, phone: +49 (0) 3693 50 5000-0, email: sales@nanoplus.com
©copyright nanoplus Nanosystems and Technologies GmbH 2025, all rights reserved. Technical data is subject to change without notice.